

扫码关注

- 
- 
- 
- ECU ( UDS DOIP)
- ECU
- CAN FD

## TC1055 Pro

|          |                       |               |                   |
|----------|-----------------------|---------------|-------------------|
|          | CAN                   | LIN           | 4                 |
| CAN      | CAN                   | 125Kbps-1Mbps | CAN FD            |
|          | 5Mbps                 | 2 LIN         |                   |
| 0-20Kbps | 4                     | T1            | 100/1000Base 2 Tx |
|          | 100Base-Tx/1000Base-T |               |                   |

TC1055Pro

USB3.0 PC

PC

Windows Linux

4 CAN CAN/CAN FD 2 LIN  
DIDO AIAO  
CAN 125Kbps-1Mbps CAN FD  
5Mbps  
LIN

TSMaster

ARXML

CAN 120Ω  
www.tosunai.com  
BLF ASC

021-59560506

sales@tosunai.cn

上海市嘉定区外冈镇嘉松北路1288弄9号楼

DoIP SOME/IP

硬件技术参数

|         |                                                                        |                                                       |            |               |
|---------|------------------------------------------------------------------------|-------------------------------------------------------|------------|---------------|
|         | 4*100/1000Base-T1 2*100Base-Tx/1000Base-T 4*CAN<br>2*LIN 4*DIDO 3*AIAO |                                                       |            |               |
| PC      | 1000Base-T/USB3.0/                                                     |                                                       |            |               |
| CAN/LIN | DB9 Male                                                               |                                                       |            |               |
| I/O     | DB9 FeMale                                                             |                                                       |            |               |
|         | TE MATENET                                                             |                                                       | H-MTD/RJ45 |               |
|         | Windows Linux                                                          |                                                       |            |               |
|         |                                                                        |                                                       |            |               |
| CAN     | CAN2.0A B                                                              |                                                       | ISO11898-1 | 125Kbps-1Mbps |
| CAN FD  | ISO                                                                    | ISO                                                   | CAN FD     | 125Kbps-5Mbps |
| LIN     | LIN1.3                                                                 | 2.x                                                   | 0-20Kbps   |               |
|         | 1us                                                                    |                                                       |            |               |
|         | CAN                                                                    | 120                                                   |            |               |
| CAN     | CAN                                                                    | DC2500V                                               |            |               |
| DIDO    | DI 0-40V                                                               | Vref:0-5V<br>:VAH=(500+499*Vref)/1098; Val=0.455*Vref |            |               |
|         | DO                                                                     | 0V                                                    | 5V/12V     |               |
| AIAO    | AI 0-10V                                                               | AO                                                    | 0-10V      |               |
|         | DC                                                                     | 9-28V                                                 |            |               |
|         | 15W                                                                    |                                                       |            |               |
|         |                                                                        |                                                       |            |               |
|         | 210*118*47mm                                                           |                                                       |            |               |
|         | 921 g                                                                  | / 2286 g                                              |            |               |
|         | -40 ~80                                                                |                                                       |            |               |
|         | 10%                                                                    | 90%                                                   |            |               |
|         |                                                                        |                                                       |            |               |

订购信息

| 产品名称 | 型号         | 功能描述 |
|------|------------|------|
|      | TC1055 Pro |      |

发货清单

- TC1055 Pro
  - 12V2A
  -
- TE MATENET
  - DB9
  - DB9
  - DB9
- - 
  - LIN
- - 
  - CAN