



TC1055Pro+

CAN LIN 4 CAN CAN  
125kbps-1Mbps CAN FD 8Mbps

CANXL 20Mbps 2 LIN  
4.8kbps-20kbps 4 100/1000Base-T1 2  
100Base-Tx/1000Base-T

MAC Bypass PHY Bypass MAC  
TC1055Pro+

CAN ETH  
CAN ETH

TC1055Pro+ USB3.0 PC

PC Windows Linux

ARXML TSMaster DBC LDF XML

SOME/IP UDS ECU CCP/XCP DoIP

· Windows Linux

· 4 100/1000Base-T1 2 100Base-Tx/1000Base-T

· 6 MAC + 4  
PHY Bypass

· 4 CAN CAN/CAN FD/CANXL

· DIDO / AIAO /

· CAN 125kbps-1Mbps CAN FD  
8Mbps CANXL 20Mbps

· 2 LIN 4.8kbps-20kbps

· LIN

· LED

· TSMaster ARXML

· CAN 120

· BLF ASC /

· DoIP SOME/IP

· CAN

	4*100/1000Base-T1 2*100Base-Tx/1000Base-T 4*CAN 2*LIN 4*DIDO 3*AIAO
PC	1000Base-T/USB3.0/
CAN/LIN	DB15Male/DB9 Male
I/O	DB9 Female
	TE MATENET/RJ45
	Windows Linux
CAN	CAN 2.0A B ISO11898-1 125kbps~1Mbps
CAN FD	ISO ISO CAN FD 125kbps~8Mbps
CAN XL	Fast 20Mbps
LIN	LIN 1.3 2.x 4.8kbps~20kbps
	100/1000Mbps
	1
	CAN 120
CAN	CAN DC2500V
	DC 9-28V
	15W
	210*118*47mm
	-40 ~ 80
	10% 90%

	TC1055 Pro+	

- TC1055 Pro+
- 12V2A
- 
- DB9
- DB9 LIN
- DB15

