



ᐃᐃ ᐃᐃᐃ

	2 × CAN/CAN FD/CAN XL
PC ᐃᐃ ᐃᐃ	USB 3.0 ᐃᐃ RJ45 ᐃᐃ
ᐃᐃ	ᐃᐃ ᐃᐃ
ᐃᐃ ᐃᐃ	% D-Sub, 9-Pin
License	ᐃᐃ TSMaster ᐃᐃ License
ᐃᐃ ᐃᐃ ᐃᐃ	ᐃᐃ ᐃᐃ ᐃᐃ
ᐃᐃ	ᐃᐃᐃᐃ USB ᐃᐃ / ᐃᐃ DC 9~26 V ᐃᐃ ᐃᐃ 12 V ᐃᐃ
ᐃᐃ ᐃᐃ	4.2 W
ESD ᐃᐃ ᐃᐃ	ᐃᐃ ᐃᐃ ᐃᐃ 4 kV ᐃᐃ ᐃᐃ ᐃᐃ 8 kV
CAN ᐃᐃ %	CAN ᐃᐃ ᐃᐃ ᐃᐃ ISO11898 -2:2024 ᐃᐃ
ᐃᐃ ᐃᐃᐃᐃ	ᐃᐃᐃᐃ CAN /CAN FD/CAN XL ᐃᐃ ᐃᐃ ᐃᐃ ISO 11898 -2:2024 ᐃᐃ
CAN ᐃᐃ ᐃᐃ ᐃᐃ	125 kbps ~ 1 Mbps ᐃᐃ
CAN ᐃᐃᐃᐃ ᐃᐃ	ᐃᐃᐃᐃ 0 ~ 8 ᐃᐃ ᐃᐃᐃᐃ ᐃᐃ
CAN FD ᐃᐃ ᐃᐃ ᐃᐃ	125 kbps ~ 8 Mbps ᐃᐃ
CAN FD ᐃᐃᐃᐃ ᐃᐃ	ᐃᐃᐃᐃ 0 ~ 64 ᐃᐃ ᐃᐃᐃᐃ ᐃᐃ
CAN XL ᐃᐃ ᐃᐃ ᐃᐃ	ᐃᐃᐃᐃ FAST ᐃᐃ ᐃᐃᐃᐃ ᐃᐃ ᐃᐃ ᐃᐃ 20 Mbps
CAN XL ᐃᐃᐃᐃ ᐃᐃ	ᐃᐃᐃᐃ 1 ~ 2048 ᐃᐃ ᐃᐃᐃᐃ ᐃᐃ
ᐃᐃ ᐃᐃ	CAN ᐃᐃ 120 ᐃᐃ ᐃᐃ ᐃᐃ ᐃᐃ
ᐃᐃ ᐃᐃ	R
ᐃᐃ ᐃᐃ	ᐃᐃ 113 × 98 × 38 mm
	ᐃᐃ 265 g
ᐃᐃ ᐃᐃ ᐃᐃ ᐃᐃ	-40 ~ 80
ᐃᐃ ᐃᐃ ᐃᐃ ᐃᐃ	10% ~ 90% ᐃᐃ

ᐃᐃ